



Height	Area	Volume	Weight
0.5	0.08	0.01	0.01
1.0	0.32	0.04	0.04
1.5	0.75	0.11	0.11
2.0	1.36	0.22	0.22
2.5	2.15	0.37	0.37
3.0	3.12	0.54	0.54

Fargeinnstilling	Enkel farge
Lysvinkel (grader)	90
Lysfluks (Lumen)	2000lm
Lysutbytte (Lm/W)	105.3
Effektfaktor	>0.95
UGR-indeks	< 23 - Generell belysning
Optisk Deksel	Opal
Produkttype	LED downlight

Armatur informasjon

Montering	Innfelt
Utsnitt (mm)	205
Beskyttelsesnivå (IP)	IP44
Beskyttelse mot Støt (IK)	IK03 - 0.35 joule
Driftstemperatur	-20 til + 40
Materiale	Aluminium
Farge på Armaturet	Hvit
Armatur Tilkobling	PI [push-in-kontakt]

Dimensjoner

Høyde (mm)	23
Diameter (mm)	217

Hvorfor kjøpe fra Lampedirekte ?

Sensor Information

Type Sensor	 Enkle og effektive LED-løsninger Ingen sensor	 Skreddersydd tilbud
	 Opptil 7 års garanti på LED-produkter	 Enkel returprosess